

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)



P.B. 5818 - Patentlaan 2
2280 HV Rijswijk (ZH)
☎ +31 70 340 2040
TX 31651 epo nl
FAX +31 70 340 3016

Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Generaldirektion 1

Directorate General 1

Direction Générale 1

Drömer, Hans-Carsten, Dr.-Ing.
Ford-Werke Aktiengesellschaft,
Patentabteilung NH/DRP,
Henry-Ford-Strasse 1
50725 Köln
DE

Eingang
18. Juni 2003
NH/DRP

01012295

Datum/Date

13/06/03

Zeichen/Ref./Réf.

page 3 of 1001

Anmeldung Nr./Application No./Demande n°/Patent Nr./Patent No./Brevet n°.

03100486.4 1268

Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire

Ford Global Technologies, Inc., @A subsidiary of Ford Motor Company

Übersendung von/Transmission of/Envoi de

Antrag vom/Request dated/Requête du 27/02/03

- ☐ Kopien bei Akteneinsicht nach Regel 94(3) EPÜ
Copies in the case of inspection of files pursuant to Rule 94(3) EPC
Copies en cas d'inspection publique selon la règle 94(3) CBE
- ☐ Beglaubigung
Certification
Certification
- ☒ 1 Prioritätsbeleg(e)/priority document(s)/document(s) de priorité R. 94(4)
- ☐ Ausfertigung(en) der Patenturkunde nach Regel 54(2) EPÜ
Duplicate of the patent certificate pursuant to Rule 54(2) EPC
Duplicata du certificat de brevet, selon la Règle 54(2) CBE
- ☐ Auszug aus dem Register nach Regel 92(3) EPÜ
Extract from the register pursuant to Rule 92(3) EPC
Extrait du registre selon la Règle 92(3) CBE
- ☐ Auskunft aus den Akten nach Regel 95 EPÜ
Communication of information contained in the files pursuant to Rule 95 EPC
Communication d'informations contenues dans la dossier selon la Règle 95 CBE
- ☐ Akteneinsicht nach Regel 94(2) EPÜ
Inspection of files pursuant to Rule 94(2) EPC
Inspection publique selon la Règle 94(2) CBE

Rechnung folgt/Invoice to follow/Facture suivra

unter Zugrundelegung von
on the basis of the following
sur la base suivante

Verwaltungsgebühr/Administration fee/Taxe d'administration

☒

Kosten für Kopien/Cost of copies/Frais pour copies (_____)

Blätter)
pages)
feuilles)

☐

Telefax

☐

☐ Zur Abbuchung vom laufenden Konto
to be debited from the deposit account
à débiter du compte courant

Nr. _____
No. _____
n° _____

KOERNER-ZALMSTRA H (TEL:2007)

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 11 November 2003



The
**Patent
Office**


1/77

The Patent Office

Cardiff Road
Newport
South Wales NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



1. Your reference 203-0264 04MAR03 F7R9188-1 002461
P01/7700 0.00-0304791.7

2. Patent application number
(The Patent Office will fill in this part)

0304791.7

3. Full name, address & postcode of the or of each applicant. (Underline all surnames)

Ford Global Technologies LLC.,
600 Parkland Towers East, One Parklane Boulevard.
Dearborn, Michigan 48126, United States of America

Patents ADP number (If you know it)

If the applicant is a corporate body, give the country / state of its incorporation

United States of America / Michigan

8578627001

4. Title of invention

AIR VENT FOR VEHICLE AIR DUCTING

5. Name of your agent (If you have one)

David Grunfeld
Ford Motor Company Limited
Room 1/445, Eagle Way, WARLEY
Essex, CM13 3BW

"Address for service" in the United Kingdom to which all correspondence should be sent (Including the postcode)

Patents ADP number (If you know it)

06826747002 ✓

6.	If you are declaring priority from one or more earlier patent applications, give the country & the date of filing of the or of each of these earlier applications & (If you know it) the or application number.	Country	Priority Application No. (If you know it)	Date of Filing (Day / Month / Year)
----	---	---------	--	--

7.	If this application is divided or otherwise derived from an earlier UK application, give the number & the filing date of the earlier application.	No. of Earlier Application	Date of Filing (Day / Month / Year)
----	---	----------------------------	--

8. Is a statement of inventorship & of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 6
Claim (s) 3
Abstract 1
Drawing (s) 3 + 3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship & right to grant of a patent (Patents Form 7/77)

Request for a preliminary examination & search (Patents Form 9/77) 1

Request for a substantive examination (Patents Form 10/77)

Any other documents 0
(Please specify)

11.

I / We request the grant of a patent on the basis of this application

Marion Gillespie

3.3.03

Signature

Date

12. Name & daytime telephone number of person to contact in the United Kingdom

Marion Gillespie
(01277) 251667

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication of communication of the invention should be prohibited or restricted under Section 22 or the Patent Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patent Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent of the same invention & either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper & write "See continuation sheet" in the relevant part (s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patent Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign & date it.
- For details of the fee & ways to pay, please contact the Patent Office.

An Air Vent for Vehicle Air Ducting

This invention relates to air vents which are used with the air ducting and ventilation systems

5 for vehicle interiors, and which are typically but not exclusively installed in the vehicle dashboard.

Air vents or nozzles are typically provided in the dashboards of motor vehicles to control the supply of air from a vehicle air ventilation and/or air conditioning system into the passenger
10 compartment of a vehicle. An air vent is therefore required to have some aesthetic properties and when closed should be visually unobtrusive and fit harmoniously with the interior trim of the vehicle.

A typical air vent, for example as shown in US 6244952 or GB 2351145, has a housing
15 having an air flow control valve at its air inlet port with vanes or ribs at the air outlet. The vanes or ribs may be moved relative to the housing and used to direct the air flow from the vent, and in some cases the directional vanes may be closed completely on each other to present an aesthetically pleasing closed surface when the vent is not in use. In US 6244952, the directional vanes are hidden by a roller blind or screen which hides the outlet when the
20 vent is not in use. The screen must be removed to permit any air flow through the vent and is displaced by an electric motor switched on by a control wheel which also operates the air flow control valve either mechanically or through the electric motor.

A disadvantage of the system is that it requires displacement of the screen to permit air flow
25 through the vent and that the air vent is operated through expensive electrical controls and motors.

The present invention provides an air vent for a vehicle air ventilation system having the directional vanes hidden behind a screen and which does not require any displacement of the screen to permit air flow, and an air vent in which the volume of air flow control and screen

5 opening mechanism are operated through a single mechanical control.

According to the present invention there is provided an air vent for a vehicle air ventilation system comprising an air inlet, an air outlet and a screen located at the air outlet, the screen being moveable from a closed condition in which air flow through the outlet is impeded to an
10 open condition allowing air flow through the outlet, characterised by at least one aperture in the screen permitting some air flow through the screen when the screen is in its closed condition.

Preferably, the screen comprises a plurality of slats. In the closed condition, each slat is in
15 contact with, or very close proximity to, an adjacent slat. A plurality of the slats are provided with apertures such that with the screen in the closed condition air can flow through the apertures.

The slats may be individually rotatable, the screen being opened by individual rotation of
20 each slat.

Vanes for directional control of the air flow may be mounted at the air outlet behind the screen.

25 Preferably, an air flow control valve is located at the air inlet.

Suitably, a control actuator is located at the air outlet, the control actuator being coupled to the air flow control valve and screen, so that after a predetermined movement of the control actuator, further movement causes movement of the screen from a closed to an open

5 condition. The connection between the control actuator and screen includes a lost motion connection.

The air flow control valve may comprise a flap valve pivotally mounted at the air inlet for rotation between open and closed positions, the flap being rotated by a lever, the lever being
10 coupled by a pivotal link to the control actuator so that movement of the control actuator causes rotation of the valve.

According to another aspect of the present invention, there is provided an air vent for a vehicle air ventilation system, the air vent comprising an air inlet and an air outlet, an air
15 flow control valve located at the air inlet, and a screen located at the air outlet, the screen having at least one aperture therein and being moveable from a closed condition in which air flow through the air outlet is impeded to an open condition allowing air flow through the air outlet, wherein a control actuator is coupled to the air flow control valve so that movement
of the control actuator operates the air flow control valve, the control actuator being further
20 coupled to the screen so that the screen is caused to move from a closed condition to an open condition only after a predetermined movement of the control actuator.

The invention will be described by way of example and with reference to the following drawings in which:

25 Fig. 1 is an isometric view of an air vent according to the present invention,

Fig. 2 is a longitudinal section through the air vent shown in Fig. 1 in a closed condition,

Fig. 3 is a longitudinal section as shown in Fig. 1 with the air vent in an impeded partial flow condition,

5 Fig. 4 is an isometric view of the air vent in an open condition,

Fig. 5 is a longitudinal section through the air vent in an open condition,

Fig. 6. is a section through the control air flow valve and slat operating mechanism in the closed condition, and

Fig. 7 is a section through the operating mechanism of Fig. 6 in the open condition.

10

With reference to Figs. 1 & 2, there is shown an air vent 10 for use in the dashboard of a motor vehicle. The air vent has a hollow housing 11 having an inlet 12 connectable to a vehicle air ventilation and/or air conditioning system and an outlet 13 through which air enters the vehicle passenger compartment.

15

An air flow control valve 15 is located at the inlet 12 to control the volume flow of air into the vent 10 and is pivoted to the housing 11 about an axis 16 at its centre, so that the valve can rotate relative to the inlet 12. The valve in the position shown in Fig. 2 completely closes the vent 10. A screen 17 is located in the inner end of the outlet 13, that is inner with respect to the vehicle. The screen 17 comprises a plurality of substantially parallel slats 18-21 that extend horizontally across the mouth of the outlet 13 and are vertically orientated. The slats 18-21 are substantially planar and are arranged so that the adjacent edges of neighbouring slats are almost in contact with, or are in close proximity to, each other. The

20

upper edges of the slats 19-21 are provided with elongate apertures or slots 22 which extend along a mid portion of the upper edges of the respective slats.

-----Immediately behind the screen 17, there is located a grille of substantially vertical vanes 24
5 linked by a central bar 25 having a slide knob 26 attached thereto. The vanes 24 are pivotally mounted in the outlet 13 and can be moved by use of the knob 26 to control the direction of the air out flow from the vent.

As is best seen in Figs 4, 6 & 7, the slats 18-21 are each pivoted to the mouth of the housing
10 by pins 27 at their respective lower edges. A control actuator comprising a wheel 28 is mounted vertically on the outside of and adjacent the housing 11, and is coupled by arm 29 to respective pins 31 at the top edge of each slat. The arm 29 is rotatable relative to the wheel and housing coaxially of the wheel axis and has four lobes 32 each of which is connected to a pin 31 at the top edge of each slat. There is a lost motion connection between
15 the arm 29 and control wheel 28 so that the control wheel 28 can rotate for a predetermined amount without movement of the slats 18-21. The lost motion connection may, for example, be provided by a pin 41 on the arm 29 engaging an elongate aperture 42 in the control wheel. Any further rotational movement beyond the predetermined degree of rotation will cause the slats to move about the axis of the pins 27.

20

The control valve 15 may comprise a flap or disc, and the axis 16 may comprise a spindle which extends across the full width of the housing, or may comprise separate stub spindles located one on each side of the flap. The spindle 16 extends through the housing and is rotationally fast with a lever 33 pivotally mounted externally of the housing. The lever 33 is
25 in turn coupled to the control wheel 28 by a link 34 which is pivoted to one end of the lever

33 and a radially outer portion of the control wheel. Rotation of the control wheel 28 causes the lever 33 to move to rotate the valve 15 about the spindle 16.

The vent 10 is shown in a closed condition in Fig. 2 and Fig. 6. The control wheel 28 is

5 rotated within said predetermined limit and partially opens the valve 15 through rotation of the lever 33 via the link 34. The arm 29 remains stationary and the pin 41 moves along the aperture 42 whilst the slats 18-21 remain closed. This is shown in Fig. 3, and air entering the vent 10 exits the outlet 13 through the slots 22 in the upper edges of the slats 19-21, thus providing an impeded air flow which may be perceived by a passenger as a gentle soft
10 breeze.

Further rotational movement of the control wheel 28 in the same direction beyond the predetermined limit causes further opening of the valve 15 and rotational movement of the arm 29 causing the slats 18-21 to move around the pins 27. The top edges of the slats 18-21
15 are moved inwardly by the arms 29 causing the slats to rotate clockwise opening large gaps as the planar slats move from a substantially vertical orientation to a substantially horizontal orientation. This is shown in Figs 4 and 5. In this condition the air vent 10 is fully open and the vanes 24 may be used to direct the air flow as is required by the passenger or driver of the vehicle.

Claims

1. An air vent for a vehicle air ventilation system comprising an air inlet, an air outlet
and a screen located at the air outlet, the screen being moveable from a closed condition in
5 which air flow through the outlet is impeded to an open condition allowing air flow through
the outlet, characterised by at least one aperture in the screen permitting some air flow
through the screen when the screen is in its closed condition.
2. An air vent as claimed in claim 1, wherein the screen comprises a plurality of slats.
- 10 3. An air vent as claimed in claim 2, wherein in the closed condition the edge of each
slat is in contact with, or close proximity to, the edge of an adjacent slat.
4. An air vent as claimed in Claim 3, wherein a plurality of the slats are provided with
15 apertures such that with the screen in the closed condition air can flow through the apertures.
5. An air vent as claimed in any one of Claims 2 to 4, wherein the slats are individually
rotatably mounted and the screen is opened by individual rotation of the slats.
- 20 6. An air vent as claimed in any preceding claim, further comprising an air flow control
valve located at the air inlet.
7. An air vent as claimed in claim 6, further comprising a control actuator located at the
air outlet, the control actuator being coupled to the air flow control valve and screen so that

after a predetermined movement of the control actuator, further movement causes movement of the screen from a closed to an open condition.

8. ~~An air vent as claimed in claim 7, wherein the control actuator is coupled to the~~
5 screen through a lost motion connection.

9. An air vent as claimed in any one of claims 6 to 8, wherein the air flow control valve comprises a flap valve pivotally mounted at the air inlet for rotation between open and closed positions, the flap being rotated through a lever.

10. An air vent as claimed in claim 9 when dependant upon claim 7 or claim 8, wherein the lever is coupled by a pivotal link to the control actuator so that movement of the control actuator causes rotation of the flap valve.

15 11. An air vent as claimed in any preceding claim, further comprising vanes for directional control of the air flow, the vanes being mounted at the air outlet behind the screen.

12. An air vent for a vehicle air ventilation system, the air vent comprising an air inlet
20 and an air outlet, an air flow control valve located at the air inlet, and a screen located at the air outlet, the screen having at least one aperture therein and being moveable from a closed condition in which air flow through the air outlet is impeded to an open condition allowing air flow through the air outlet, wherein a control actuator is coupled to the air flow control valve so that movement of the control actuator operates the air flow control valve, the control
25 actuator being further coupled to the screen so that the screen is caused to move from a

closed condition to an open condition only after a predetermined movement of the control actuator.

13. An air vent for a vehicle air ventilation system substantially as described herein with
5 reference to figures 1-7.

10

15

20

25

Abstract**An Air Vent for Vehicle Air Ducting**

5



An air vent 10 for a vehicle air ventilation system and which comprises a housing 11 having an air inlet 12 and an air outlet 13, an air flow control valve 15 located in the inlet 12, and a

screen 17 comprising a plurality of slats 18-21 located in the outlet 13. The slats are moveable by a control wheel 28 from a closed condition, in which air flow through the outlet

10

13 is impeded, to an open condition allowing air flow through the outlet 13, the control wheel 28 also operating the valve 15 to permit the flow of air prior to opening the slats, the air flow passing through slots 22 in at least some of the slats.

Fig. 3



THIS PAGE BLANK (USPTO)

2/3




FIG 3




FIG 4




FIG 5

THIS PAGE BLANK (USPTO)

CLOSED POSITION




FIG 6

OPEN POSITION




FIG. 7

THIS PAGE BLANK (USPTO)